

# FLIR LATITUDE™ 9.2

Network Video Management System (VMS)  
for the United VMS (UVMS) Family



FLIR Latitude is an enterprise-level IP surveillance system with forensic-quality imaging and a flexible, modular operator interface. Using the latest technology, FLIR Latitude is a powerful and versatile network VMS featuring enhanced cyber security, edge device integration, and global administration. The scalable architecture efficiently supports systems of any size, and it can be implemented throughout an enterprise spanning multiple sites, cities, and continents.

[www.flir.com/latitude](http://www.flir.com/latitude)

## SCALABLE, ENTERPRISE-LEVEL VMS

Advanced VMS architecture

- Open platform supports a wide range and virtually unlimited number of cameras and edge devices
- Architecture allows system growth and full use of current server and client PC hardware to reduce cost of ownership
- Incorporates the latest video technologies: GPU-assisted decoding, H264/265 compression, upgraded ONVIF support
- Cyber security meets today's evolving threat landscape including dynamic keys and hardened server-server, server-client, and server-edge device communication

## ENTERPRISE-LEVEL TECHNOLOGY

Complete solution meets the needs of sophisticated systems

- Simplifies video operations management (combining FLIR Latitude with storage and edge devices) for a unified and cost-effective system
- Supports FLIR edge devices in visible, thermal, and radar domains, and various third-party technologies including Storage-on-the-Edge (SoE) integration, GIS systems, access control, augmented systems, gunshot detection, vehicle and human recognition, condition monitoring, and cloud connectivity
- Expanded FLIR Cloud connectivity and functionality provide a platform to support future enhancements
- Video wall management option improves command and control center usage

## USER-FRIENDLY INTERFACE AND DESIGN

Powerful feature set with easy-to-use controls

- Intuitive UI/UX combines advanced forensic functionality for quicker access and playback of event footage with a streamlined design for operator efficiency
- Powerful set-up, control, and installation capability for configuring and running small and large systems
- Proactive system health monitoring tool maintains system operation and uptime
- Full-featured HTML5 web client offers complete browser access

## SYSTEM REQUIREMENTS

Server Requirements	Minimum	Recommended
Operating System	Windows Server 2016	Windows Server 2019
Processor	Intel® Core™ Skylake i5-6500 or better	Intel® Silver 4208 or better
RAM	8 GB	16 GB
System Storage	7200 RPM; 80 GB for OS+SW	7200 RPM; 80 GB for OS+SW; 50 GB for DB
Video Storage	7200 RPM; Standalone configured as independent physical and logical drive(s)	7200 RPM; (1) RAID 5 Array; (1) Global Hot Spare
Network Interface	(1) 1 Gbps	(1) 1 Gbps

\*Server requirements may vary. Please reference "Latitude-9.2-Server-Specifications" for advanced specifications.

Client Requirements	Minimum	Recommended
Operating System	Windows 10 64-bit	Windows 10 Version 20H2
Processor	Intel® Xeon™ E3-1245 @ 3.30 GHz or better	Intel® Core™ i3-10105 CPU @ 3.70 GHz or better
RAM	8 GB	16 GB
System Storage	5400 RPM; 125 GB for OS+SW	SSD 240 GB for OS+SW
Network Interface	1 Gbps	1 Gbps
Video Card	Intel® HD 4000 Series	NVIDIA T400

## Licensing Options

License	Video Channels
Classic	Up to 70
Elite	Up to 250
Enterprise	Unlimited
Basic Licensing Features	All base licenses include the following: Five user connections, Five EZ client connections, and Full functionality

The following items need to be ordered separately:

- Additional video channel connections
- Additional user connections
- Mobile user connections
- Failover
- Redundancy
- GIS map support
- SDK, DSF, and RTSP connection
- Integrations to third-party systems
- Global Admin License
- Radar Support
- Condition Monitoring

\*Note:

For ordering and hardware specification information, please refer to the FLIR Price Guide and the Latitude System Specification Document. Both can be obtained by contacting your Local Regional Sales Manager.

Specifications are subject to change without notice. For the most up-to-date specs, go to [www.flir.com/latitude](http://www.flir.com/latitude)

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited. For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2021 Teledyne FLIR, LLC. All rights reserved.

Revised on 04/12/22  
Lateral\_Datasheet\_LTR\_20-0013

For more information contact: [Sales@TeledyneFLIR.com](mailto:Sales@TeledyneFLIR.com)  
or to find your local support number, visit: [flir.com/contactsupport](http://flir.com/contactsupport)