



OUTDOOR THERMAL MONOCULAR

FLIR Scion™ OTM

The FLIR Scion™ OTM leverages high-performance thermal imaging and a refined user interface to quickly detect objects of interest and provide superior awareness in low visibility conditions. Built around FLIR's powerful Boson core, the Scion OTM produces smooth thermal imaging up to 60 Hz and captures geotagged video and still images for playback long after the day is done. A rugged, IP67-rated housing and intuitive controls allow single-hand operation in harsh weather conditions, maintaining reliable thermal imaging in the most demanding outdoor environments.

www.flir.com



ONBOARD VIDEO AND IMAGE RECORDING

Revisit every wildlife encounter in sharp, smooth thermal imaging

The Scion OTM is ready to capture any wildlife encounter with onboard video and image recording. Smooth 60 Hz thermal imaging preserves details on moving objects while internal storage and a built-in microSD™ card slot provide enough memory for the most demanding trips. Additional Bluetooth and Wi-Fi capabilities allow simple file transfer between devices.



REDESIGNED USER INTERFACE

The Scion OTM's polished user interface packs functionality into a rugged handheld optic

Intuitive controls and revamped internal menus allow quick thermal palette adjustments and provide easy access to new features such as picture-in-picture zoom, video recording, and GPS functionality. A rugged IP67-rated housing stands up to the elements and protects key hardware components.



TRUSTED THERMAL DETECTION


Powered by FLIR's breakthrough Boson thermal core

Able to perform at any time of day, thermal imaging pierces complete darkness, glaring light, and lingering haze to provide superior awareness in difficult conditions. The advanced image processing of FLIR's Boson thermal core paired with a 60 Hz image refresh rate provide smooth, unwavering vision in challenging environments.

SPECIFICATIONS

General	Scion OTM136	Scion OTM236	Scion OTM266	Scion OTM366
Core Technology	BOSON 12 μ m VOx Microbolometer			
Detector Resolution	320 x 256		640 x 512	
Lens System	13.8 mm	18 mm		25 mm
Field of View (H x W)	16° x 12°	12° x 9°	24° x 18°	18° x 13°
Optical Magnification	1.5x	1.9x	1x	1.3x
Digital Zoom	1X 2X 4X		1X 2X 4X 8X	
Refresh Rate	60 Hz			
Video Recording	Yes			
Image Capturing	Yes			
Internal Memory	2 GB Internal Storage / Optional microSD™ Card (up to 128 GB)			
Focus	∞		Manual	
Eye Relief	16 mm			
Display	Quad-VGA (1280x960) High definition display			
Display Focus	Manual			
User Interface				
Temperature Imaging Modes (Thermal Palettes)	White Hot; Black Hot; Iron Bow; Rainbow; Graded Fire; Lava			
Viewing Modes	Scouting, Picture-in-Picture			
Picture While Recording (PWR)	Yes			
Date/Time Stamp	Yes			
Auto Power OFF	Yes			
Magnetic Compass	Yes			
Accelerometer	Yes			
Interfacing				
USB Type	USB-C; Power In; Video Out; Video and Image File Transfer			
Power				
Battery Life	Up to 4.5 hours at 20°			
Battery Type	6x CR123A 3V Lithium Battery			

	Scion OTM136	Scion OTM236	Scion OTM266	Scion OTM366
Communications				
NFC (Near-Field Communications)	Yes			
Bluetooth™	BLE 4.1+			
Wi-Fi	Video Streaming			
GPS	No		Yes	
Physical				
Size	239 x 76.8 x 60.5 mm (9 x 3 x 2.4 in)		227 x 76.8 x 60.5 mm (9.4 x 3 x 2.4 in)	
Weight	With Batteries: 452 g; Without Batteries 572 g			
Color (Housing)	Green / Black			
Mounting	¼-20 Tripod Mount			



Specifications are subject to change without notice. For the most up-to-date specs, go to www.flir.com

FLIR OUTDOOR & TACTICAL SYSTEMS

9 Townsend West,
Nashua, NH 03063

Phone: 1-888-959-2259
or (603) 324-7600
Fax: 1-888-959-2260

FLIR PRODUCT REPAIR CENTER

email: US_CBUrepair@flir.com
Register on: customer.flir.com

ORDER PLACEMENT, RETURN TO STOCK & INQUIRIES

email: OTS-Orders@flir.com

PRODUCT REGISTRATION

flir.com/support-center/support-hq/

TECHNICAL SUPPORT

email: US_CBUsupport@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 5/19

18-2850-OTS-SCION-OTM



The World's Sixth Sense®